

PRODUCT-DETAILS

# ESB25-04N-01

## ESB25-04N-01 Installation Contactor



### General Information

Extended Product Type	ESB25-04N-01
Product ID	1SAE231111R0104
EAN	4013614517617
Catalog Description	ESB25-04N-01 Installation Contactor
Long Description	<p>The ESB25..N installation contactors are used to control single and three-phase loads up to 25 A and can be operated by AC or DC voltages.</p> <p>These contactors are made for use in household applications as well as in industrial environments.</p> <p>The following benefits are provided: Hum-free operation, low power consumption and integrated overvoltage protection. Various contact combinations and accessories are available.</p>

### Ordering

Package Level 1 EAN	4013614523915
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

### Popular Downloads

Instructions and Manuals	2CDC103043M6801
--------------------------	-----------------

**Dimensions**

Product Net Width	36 mm
Product Net Height	85 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.245 kg

**Technical**

Rated Operational Voltage	Main Circuit 220 V DC Main Circuit 400 V AC
Rated Control Circuit Voltage (U <sub>c</sub> )	24 V
Rated Frequency (f)	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Control Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Rated Operational Current AC-1 (I <sub>e</sub> )	(NC) 25 A
Rated Operational Current AC-3 (I <sub>e</sub> )	(230 V) Single Phase, NC 6 A
Rated Operational Power AC-1 (P <sub>e</sub> )	(230 V) Single Phase, NC 5.8 kW (400 V) Three Phase, NC 17.3 kW
Rated Operational Power AC-3 (P <sub>e</sub> )	(230 V) Single Phase, NC 0.9 kW (400 V) Three Phase, NC 2.7 kW
Rated Operational Current AC-7a (I <sub>e</sub> )	(NC) 25 A
Rated Operational Power AC-7a (P <sub>e</sub> )	(230 V) Single Phase, NC 5.8 kW (400 V) Three Phase, NC 17.25 kW
Rated Operational Current AC-7b (I <sub>e</sub> )	(400 V) Three Phase, NC 6 A
Rated Operational Power AC-7b (P <sub>e</sub> )	(230 V) Single Phase, NC 2.7 kW (400 V) Three Phase, NC 2.7 kW
Recommended Screw Driver	Control Circuit Pozidriv 1 Main Circuit Pozidriv 1
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 500 V
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 1.5 ... 10 mm <sup>2</sup> Flexible with Ferrule 2x 1.5 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 1.5 ... 10 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 1.5 mm <sup>2</sup> Flexible 1x 1.5 ... 10 mm <sup>2</sup> Flexible 2x 1.5 ... 4 mm <sup>2</sup> Rigid 1x 1.5 ... 10 mm <sup>2</sup> Rigid 2x 1.5 ... 4 mm <sup>2</sup>
Connecting Capacity Control Circuit	Flexible with Ferrule 1x 1 ... 2.5 mm <sup>2</sup> Flexible with Ferrule 2x 0.75 ... 1 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 1 mm <sup>2</sup> Flexible 1x 1 ... 4.0 mm <sup>2</sup> Flexible 2x 1 ... 2.5 mm <sup>2</sup> Rigid 1x 1 ... 4 mm <sup>2</sup> Rigid 2x 1 ... 2.5 mm <sup>2</sup>
Tightening Torque	Control Circuit 0.9 N·m Main Circuit 1 N·m
Wire Stripping Length	Control Circuit 7 mm Main Circuit 10 mm
Degree of Protection	IP20
Mechanical Durability	1000000 cycle

Number of Poles	4
Number of Main Contacts NC	4
Number of Main Contacts NO	0
Width in Number of Modular Spacings	2
Pollution Degree	3
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 61095 UL 60947-1 UL 60947-4-1

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 480 V AC
Horsepower Rating UL/CSA	(220 ... 240 V AC) Single Phase, NC 1 Hp (220 ... 240 V AC) Three Phase, NC 3 Hp (440 ... 480 V AC) Single Phase, NC 0.5 Hp (440 ... 480 V AC) Three Phase, NC 2 Hp
Connecting Capacity Main Circuit UL/CSA	Solid 16-8 AWG Stranded 16-8 AWG
Connecting Capacity Control Circuit UL/CSA	Solid 16-10 AWG Stranded 16-10 AWG
Tightening Torque UL/CSA	Control Circuit 8 in-lb Main Circuit 9 in-lb

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
RoHS Status	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

ABS Certificate	1SAA920000-0101
CB Certificate	1SAA920004-2001
CCC Certificate	1SAA920002-3801
cULus Certificate	cUL_E191658
Declaration of Conformity - CE	1SAD938504-0302
DNV Certificate	1SAA920000-0306
EAC Certificate	1SAA920001-2702
Instructions and Manuals	2CDC103043M6801
RINA Certificate	1SAA920000-0801
RMRS Certificate	1SAA920000-0705
RoHS Information	1SAD938503-0302

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	39 mm
Package Level 1 Height	92 mm

Package Level 1 Depth / Length	69.5 mm
Package Level 1 Gross Weight	0.245 kg
Package Level 1 EAN	4013614523915
Package Level 2 Units	60 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	15.4 kg
Package Level 2 EAN	4013614538315

## Classifications

Object Classification Code	Q
ETIM 5	EC001653 - Installation contactor for distribution board
ETIM 6	EC001653 - Installation contactor for distribution board
ETIM 7	EC001653 - Installation contactor for distribution board
eClass	7.0 27142308
UNSPSC	39121529
E-Number (Sweden)	3210562

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Installation Contactors

Low Voltage Products and Systems → Modular DIN Rail Products → Modular DIN Rail Components MDRCs → Installation Contactors

