

PRODUCT-DETAILS

E6.2H/f 5000 Ekip Touch LI 4p F HR

E6.2H/f 5000 Ekip Touch LI 4p F HR



General Information

Extended Product Type	E6.2H/f 5000 Ekip Touch LI 4p F HR
Product ID	1SDA071984R1
EAN	8015644758349
Catalog Description	E6.2H/f 5000 Ekip Touch LI 4p F HR
Long Description	C.BREAKER SACE EMAX2 E6.2H/f 5000 FIXED FOUR-POLE FULL SIZE NEUTRAL WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/TOUCH-LI R 5000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN	8015644758349
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	1014 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	140 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1257 mm
Package Level 1 Gross Weight	151 kg
Package Level 1 EAN	8015644758349

Additional Information

Current Type	AC
Electrical Durability	Ue = < 440 V 3000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4 / f
Power Loss	483 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (Ics)	100 %
Rated Current (In)	5000 A
Rated Voltage (Ur)	690 V
Rated Impulse Withstand Voltage (Uimp)	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (Ui)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics)	(220 V AC) 100 kA (230 V AC) 100 kA (380 V AC) 100 kA (400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Short-time Withstand Current (Icw)	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (Icu)	(400 V AC) 100 kA (415 V AC) 100 kA (440 V AC) 100 kA (500 V AC) 100 kA (525 V AC) 100 kA (690 V AC) 100 kA
Rated Uninterrupted Current (Iu)	5000 A
Release Type	EL
Standards	IEC
Sub-type	E6.2
Terminal Connection Type	Rear flat Horizontal
Version	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	1SDL000165R0022
Environmental Information	Not Available
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R0002

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

