


CDB25



connectwell
THE RIGHT CONNECTION

Modular Distribution Blocks with 25 sq.mm Output connections and 50 sq.mm Bolt Type Input Connection

The CDB range of distribution blocks is an ideal choice for a simplified distribution system. A bolt in the center of the block provides a connection point for the incoming cable. All the terminals are internally connected and provide multiple connection points for the outgoing wires. A Protective shield effectively shrouds the incoming connection.

TECHNICAL DATA

Rated Voltage	800 V
Rated Current - Input Side	150 A
Rated Current - Output Side	75 A
Tightening Torque - Input Side	6 Nm
Tightening Torque - Output Side	2 Nm
Housing Material	Polymide
Product Function	Modular Distribution Blocks with Bolt Type Input Connection
Wire Entry Orientation	Side Entry
Mounting Possibility	DIN 32/DIN 35/DIN 35-15 Rail
Screw Size	M5
Stud Size	M8
Operated by	Screwdriver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	6 mm ²
Conductor Cross Section Stranded max.	25 mm ²
Conductor Cross Section Stranded min.- Input Side	10 mm ²
Conductor Cross Section Stranded max. - Input Side	50 mm ²
Conductor Cross Section Stranded min.- Output Side	6 mm ²
Conductor Cross Section Stranded max.- Output Side	25 mm ²
Conductor Cross Section AWG/Kcmil min	12 AWG
Conductor Cross Section AWG/Kcmil max	2/0 AWG
Conductor Cross Section Stranded with Ferrule/Lug min	6 mm ²
Conductor Cross Section Stranded with Ferrule/Lug max	25 mm ²
2 Conductors with same Cross Section Stranded min	6 mm ²
2 Conductor with same Cross Section Stranded max	16 mm ²
2 Conductors with same Cross Section Stranded with TWIN Ferrule/Lug min	6 mm ²
2 Conductor with same Cross Section Stranded with TWIN Ferrule/Lug max	16 mm ²
Stripping Length	14 mm
Internal Cylindrical Guage	A8

DIMENSIONS

Height with DIN 32 rail	62.3 mm
Height with DIN 35 x 15 mm rail	64.7 mm
Height with DIN 35 x 7.5 mm rail	57.2 mm
Length	49 mm
Width (Thickness)	mm


ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CDB25/1	Grey colour Modular Distribution Terminal Block with 4 outputs of 25 sq.mm	10
CDB25/2	Grey colour Modular Distribution Terminal Block with 8 outputs of 25 sq.mm	10
CDB25/3	Grey colour Modular Distribution Terminal Block with 12 outputs of 25 sq.mm	10
CDB25/4	Grey colour Modular Distribution Terminal Block with 16 outputs of 25 sq.mm	5

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA501-1M	Din 32 Rail unslotted 1 meter	50
	CA501-1M-S	Din 32 Rail slotted 1 meter	50
	CA501-2M	Din 32 Rail unslotted 2 meter	50
	CA501-2M-S	Din 32 Rail slotted 2 meter	50
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50

CDB25



connectwell
THE RIGHT CONNECTION

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA509/K12	Marking Tag Blank suitable for CTS16U / CTS25UN / CGT16N / CDB25 / CMDB25 / CSC16T / CSCG16T / CY16 / CYG16 Terminal Blocks	100
	SCS1/5.5	Electricians Screwdriver for slotted screws	10
	MC12	MARKER CARD 12MM PITCH WITH 36 TAGS	10

APPROVALS



NOTES

Sum of outgoing currents on either side of the center should not exceed half the maximum permissible incoming current.

Sum of total outgoing currents should not exceed maximum permissible incoming current.

Connection for higher outgoing currents should be done through the terminal nearest to the incoming connection.

This Terminal Blocks are available in Red, Yellow, Blue, Black & Green colours.
2) The Rated current is with the use of copper (Cu) conductor/Wire

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	DIN EN60947-7-1	CSA C.22.2 No:158
Approvals	UL	CE	CSA
Conductor Cross Section Stranded min.- Input Side	6 AWG	10 mm ²	6 AWG
Conductor Cross Section Stranded max. - Input Side	2/0 AWG	50 mm ²	2/0 AWG
Conductor Cross Section Stranded min.- Output Side	12 AWG	6 mm ²	12 AWG
Conductor Cross Section Stranded max.- Output Side	2 AWG	25 mm ²	2 AWG
Rated Voltage	600 V	800 V	600 V
Rated Current - Input Side	150 A	150 A	150 A
Rated Current - Output Side	75 A	75 A	150 A
Tightening Torque - Input Side	53 lb-in	6 Nm	53 lb-in
Tightening Torque - Output Side	22 lb-in	2 Nm	22 lb-in