

CX10/3



connectwell
THE RIGHT CONNECTION

10 sq.mm Spring Clamp Feed Through compact Terminal Blocks

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	57 A
Housing Material	Polymide
Product Function	Feed Through
Wire Entry Orientation	Side
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	8 KV
Pollution Degree	3

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	10 mm ²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	6 mm ²
Stripping Length	18 mm

DIMENSIONS

Height with DIN 35 x 15 mm rail	56.2 mm
Height with DIN 35 x 7.5 mm rail	48.7 mm
Length	97.6 mm
Width (Thickness)	10 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CX10/3	10 sq.mm Feed Through Spring Clamp Terminal Block in Grey colour	50
CX10/3BU	10 sq.mm Feed Through Spring Clamp Terminal Block in Blue colour	50
CX10/3BK	10 sq.mm Feed Through Spring Clamp Terminal Block in Black colour	50
CX10/3O	10 sq.mm Feed Through Spring Clamp Terminal Block in Orange colour	50
CX10/3R	10 sq.mm Feed Through Spring Clamp Terminal Block in Red colour	50
CX10/3Y	10 sq.mm Feed Through Spring Clamp Terminal Block in Yellow colour	50


ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	SCS0,8/4	Electricians Screwdriver for slotted screws	10
	EPCX10/3	End Plate for EPCX10/3	50
	CA509/K10	Marking Tag Blank suitable for CTS10U / CGT10U / CGT10N / CHV10U / CTS10USC / STH4 / STH4DT / STH4DTSH / CSC10T Terminal Blocks	100
	WLX10	Shockproof warning label for CX10 series.	20
	JX10/2	Shorting Link for 10 mm wide TB	20
	JXS10/2.5	Step Down Shorting Link for CX series	10
	MC10	MARKER CARD 10MM PITCH WITH 42 TAGS	10

CX10/3



connectwell
THE RIGHT CONNECTION

APPROVALS



NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	IEC/EN60947-7-1
Conductor Cross Section Stranded min.	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	6 AWG	10 mm ²
Rated Voltage	600 V	1000 V
Rated Current	65 A	57 A