CXAF4/3L



connectwell
THE RIGHT CONNECTION

4 sq.mm 3 wire Automotive Fuse with Led Compact Spring Clamp Terminal Blocks

The Spring Clamp is operated by using a screw driver to provide an access to the wire through an opening in the spring clamp. The inserted wire gets clamped on to the current bar when the screw driver is removed.

TECHNICAL DATA	
Rated Voltage	1000 V
Rated Current	10 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Single Level Fuse
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Operated by	Screw Driver
Rated Surge Voltage	4 KV
Pollution Degree	3

CONNECTION DATA	
Conductor Cross Section Stranded min.	0.2 mm²
Conductor Cross Section Stranded max.	4 mm²
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 mm²
Stripping Length	10 mm

DIMENSIONS	
Height with DIN 35 x 15 mm rail	50.7 mm
Height with DIN 35 x 7.5 mm rail	43.2 mm
Length	86.2 mm
Width (Thickness)	6 mm

FUSE SPECIFICATIONS	
Fuse Type	Blade Type
Fuse Size	ATO Regular Fuse - 19.1 × 5.1 × 18.5 mm
Fuse Current Rating	10 A

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CXAF4/3L12V	4sqmm 3 wire Automotive Fuse Terminal Block with 12V indication	50
CXAF4/3L24V	4sqmm 3 wire Automotive Fuse Terminal Block with 24V indication	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	EPCX4/4O	End Plate in Orange colour	50
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA702	End Clamp in Polyamide 66 suitable for Din 32 / Din 35 / Din 35-15 Rails	50
	CA802	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	50
	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
	JX4/16	Shorting Link for 6 mm wide TB	10
	CA509/K6	Blank Marking Tag	100
	SCS0.6/3.5	Electricians Screwdriver for slotted screws	10
	PPCX4/4	Partition Plate in Grey colour	50
	MC6	MARKER CARD 6MM PITCH WITH 72 TAGS	10

CONNECTWELL INDUSTRIES PVT. LTD. | D7, Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India - 421 204.
Tel.: +91 251 7120 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com | Website: www.connectwell.com



connectwell
THE RIGHT CONNECTION

APPROVALS

NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

RATINGS AS PER STANDARDS			
STANDARDS	**UL 1059**	**CSA C.22.2 No:158**	**IEC/EN60947-7-1**
Approvals	UL	CSA	CE
Conductor Cross Section Stranded min.	24 AWG	24 AWG	0.2 mm²
Conductor Cross Section Stranded max.	10 AWG	10 AWG	4 mm²
Rated Voltage	600 V	600 V	1000 V
Rated Current	10 A	10 A	10 A

CONNECTWELL INDUSTRIES PVT. LTD. | D7, Phase 2, M.I.D.C., Dombivli (E), Maharashtra, India - 421 204.
Tel.: +91 251 7120 600 | Fax: +91 251 7120 700 | Email: connect@connectwell.com | Website: www.connectwell.com